



**APPROVED INSTALLATION TOOLS**

# APPROVED INSTALLATION TOOLS

## SANITARY AND HEATING INSTALLATIONS

These specifications define the pressing tools approved by FRABO for **sanitary and heating installations** for the following press systems:

- FRABOPRESS SECURFRABO
- FRABOPRESS H2O SECURFRABO
- FRABO SOLARPRESS
- FRABOPRESS 316 SECURFRABO
- FRABOPRESS C-STEEL SECURFRABO

Dimensions	Manufacturer	Pressing tool	Jaws/Chains
12-28 mm	Novopress	AFP101 (9.6 V) ACO102 (12V)	PB1 jaws FB and V profiles: 12-28 mm (AFP101/ACO102)
12-54 mm		ECO201/202/203 (230V) ACO1 Pressboy (12V) ACO3 Pressmax (12V) ACO201 (12V) ACO202/203 (18V) ACO202XL / ACO203XL EFP2 (230V) EFP201/202(230V) AFP201/202 (14,4V)	PB2 ECOTEC jaws FB and V profiles: 12-35 mm  Frabo chains 42 and 54 mm (with ZB201/ZB203 adaptor)  "Snap on" chains Frabo 42 and 54 mm (with ZB201/ ZB203 adaptor)
42-54 mm		ECO301 (230V) ECO3 Pressmax (230V)	Frabo chains 42 and 54 mm (with ZB302/ZB303 adaptor) "Snap on" chains Frabo 42 and 54 mm (with ZB303 adaptor)
12-28 mm	Rothenberger	Romax Compact (12V)	Romax Compact jaws: 12-28 mm
12-54 mm		Romax Pressliner (12V) Romax Pressliner ECO (12V) Romax AC Eco (230V) Romax 3000/Romax 4000 (18V)	Rothenberger jaws: SV 12-54 mm "Snap on" chains SV42 and SV54 mm (with ZBS1 adap- tor)
12-28 mm	Klauke	Mini (9,6V) MAP2L Klauke Mini (18V)	Klauke mini jaws 12-28 mm (KSP4) or 28 mm jaw (KSP4)
12-54 mm		UAP2 (12V) UNP2 (230V) UP75 (12V) UAP3L (18V) UAP4 (12V) UAP4L (18V)	Klauke jaws: 12-54 (KSP4) and 42-54 chains (KSP4) with SBK4254 adaptor  Novopress chains: 42-54 mm and ZB201/ZB203 adaptor

Continued overleaf....

Dimensions	Manufacturer	Pressing tool	Jaws/Chains
12-54 mm	Ridgid	RP 10-S (230V) RP 300 (230V) RP 300-B (12V) RP 10-B (12V)	Ridgid jaws: 12-54 mm
12-35 mm	REMS	Mini Press ACC (12V)	REMS Mini Press jaws: 12-35 mm
12-54 mm		Powerpress (2000) (230V) Powerpress E (230V) Powerpress ACC (230V) Akku-Press (12V) Akku-Press ACC (12V)	REMS Press jaws: 12-54 mm Novopress jaws PB2 12-35 mm and 42-54 mm chains (with ZB201/ZB203 adaptor)
12-35 mm	Roller	Multi-Press Mini ACC (12V)	Roller Press Mini jaws: 12-35 mm
12-54 mm		Roller Uni-Press (230V) Uni-Press E (230V) Uni-Press ACC (230V) Multi-Press (12V) Multi-Press ACC (12V)	Roller jaws: 12-35 mm Novopress jaws (PB2 V profile) 12-35 mm and 42-54 mm chains V profile (with ZB201/ZB203 adaptor)
12-54 mm	Nussbaum	Type 5A Type 5	Jaws Nussbaum: 12-54 mm
12-28 mm	Viega	Picco	Viega Picco jaws: 12-28 mm
12-54 mm		Pressgun 4E (18V) Pressgun 4B (230V) PT3-EH (230V) PT3-AH (12V) PT2-EH (230V)	Viega PT2 jaws: 12-54 mm
12-54 mm	Geberit	PWH 75	Novopress jaws FB profile:12-35 mm Novopress-Frabo chains 42 and 54 mm (with ZB201/ ZB203 adaptor)

## GAS INSTALLATIONS

These specifications define the pressing tools approved by FRABO for gas installations for the following press systems:

- FRABOPRESS SECURFRABO
- FRABOPRESS GAS
- FRABOPRESS 316 GAS
- FRABOPRESS C-STEEL GAS

Dimensions	Manufacturer	Pressing tool	Jaws/Chains
12-28 mm	Novopress	AFP101 (9.6 V) ACO102 (12V)	PB1 jaws FB and V profiles: 12-28 mm (AFP101/ACO102)
12-54 mm		EC0201/202/203 (230V) AC01 Pressboy (12V) AC03 Pressmax (12V) AC0201 (12V) AC0202/203(18V) EFP2 (230V) EFP201/202(230V) AFP201/202 (14,4V) AC0202XL/AC0203XL	PB2 ECOTEC jaws FB and V profiles: 12-35 mm  Frabo chains 42 and 54 mm (with ZB201/203 adaptor)  "Snap on" chains Frabo 42 and 54 mm (with ZB201/ ZB203 adaptor)
42-54 mm		EC0301 (230V) EC03 Pressmax (230V)	Frabo chains 42 and 54 mm (with ZB302/ZB303 adaptor)  "Snap on" chains Frabo 42 and 54 mm (with ZB303 adaptor)
12-28 mm	Rothenberger	Romax Compact	Romax Compact jaws: 12-28 mm
12-54 mm		Romax 3000 / Romax 4000 Romax AC ECO	Rothenberger jaws: SV 12-35 mm  "Snap on" chains SV42 and SV54 mm (with ZBS1 adap- tor)
12-28 mm	Klauke	Mini (9,6V) MAP2L Klauke Mini (18V)	Klauke mini jaws 12-28 mm (KSP4) or 28 mm jaw (KSP4)
12-54 mm		UAP2 (12V) UNP2 (230V) UP75 (12V) UAP3L (18V) UAP4 (12V) UAP4L (18V)	Klauke jaws: 12-35 (KSP4) and 42-54 chains (KSP4) with SBK4254 adaptor Novopress chains: 42-54 mm and ZB201/ZB203 adaptor

Continued overleaf....

Dimensions	Manufacturer	Pressing tool	Jaws/Chains
12-35 mm	Rems	Mini Press ACC (12V)	REMS Mini Press jaws: 12-28 mm
12-54 mm		Powerpress (2000) (230V) Powerpress E (230V) Powerpress ACC (230V) Akku-Press (12V) Akku-Press ACC (12V)	REMS Press jaws: 12-35 mm  Novopress jaws PB2 12-35 mm and 42- 54 mm chains (with ZB201/ZB203 adaptor)
12-54 mm	Ridgid	RP 10-S (230V) RP 300 (230V) RP 300-B (12V) RP 10-B (12V)	Ridgid jaws: 12-35 mm
12-54 mm	Viega	Typ2 Typ3 PT3AH Akku Press - Handy	Viega PT2 jaws: 12-54 mm

## RECIPROCAL COMPATIBILITY OF TOOLS PRODUCED BY DIFFERENT MANUFACTURERS

It is known that different press manufacturers have standardised the chuck head so that it is also compatible with jaws made by other manufacturers.

Despite this situation FRABO S.p.A. strongly advises against using machines and jaws made by different companies unless a specific technical compatibility declaration is provided for the tools drawn up by the manufacturer.

## MAINTENANCE OF PRESSING TOOLS

The pressing tools and jaws/chains are subject to wear due to use, therefore regular maintenance must be carried out according to the intervals established by the manufacturer. In this way, the best installation conditions of the fittings can be guaranteed and danger of sudden breaking can be avoided, which could be dangerous for the user.

It is good practice to periodically check that the jaws/chains are not damaged or worn. In that case the jaws/chains must not be used any longer and must be sent to an authorised service centre by the tool manufacturer for the relevant checks.



**FRA.BO** s.p.A.

HEADQUARTER Via Cadorna, 30 - 25027 Quinzano d'Oglio (BS) - Italy  
MANUFACTURING UNIT Via Circonvallazione, 7- 26020 Bordolano (CR) - Italy

T +39 030 99 25 711 F +39 030 99 24 127 @ info@frabo.com W www.frabo.com